



Address: 8 Manburgh Terrace
Darra Qld. 4076
Postal Address: P.O. Box 3045
Address: Darra Qld. 4076
Phone: +61 (7) 3375 3199
Facsimile: +61 (7) 3375 3886
E-mail: info@luxurypaints.com.au

Date Issued: 1 December, 2011
Page 1 of 2

LP0002

EASI SEALER UNDERCOAT

Product Line: 15

Product Code: 1505; 1501; 1502; 1504; 1510; 1520.

Australian Paint Approval Scheme: 0172 (formerly GPC-S-17/2)

Description

A premium quality, water based acrylic sealer and undercoat, designed for interior use only. It provides a smooth sealed surface suitable for finishing with water or oil based topcoats. Special features include: easy sanding properties with good gloss hold out. Can be used economically as a sealer and undercoat for most interior work.

Easi Sealer Undercoat is suitable for sealing and undercoating interior masonry, plaster and paper faced wallboards.

Typical Specifications

Surface	Preparation	System	Dry Film Thickness
Plasterboard	Fill joints. Remove sanding dust.	First Coat: Easi Sealer Undercoat Top Coat: 2 coats Easi Clean Interior	30 - 40µm 50 - 60µm
Masonry, brick, concrete blockwork, fibre cement board	Remove any contaminants.	First Coat: Easi Sealer Undercoat Top Coat: 2 coats Easi Clean Interior	30 - 40µm 50 - 60µm

SURFACE PREPARATION

All surfaces must be dry, well prepared and free from dirt, oil, grease and other contaminants.

NEW UNPAINTED SURFACES

Fill any nail holes, cracks and surface imperfections with appropriate patching material. Sand and dust area ensuring the surface is clean and dust free. Seal plaster surfaces with 1 coat of Easi Sealer Undercoat.

PREVIOUSLY PAINTED SURFACES

Sand any previously painted areas to remove glossy surfaces and to enable adhesion of further finishing coats. Clean all surfaces ensuring all loose dust, grease, mould or flaking paint is removed. Wash with Sugar Soap. Treat mould with a suitable mould killer and rinse clean. Allow the surface to dry. Fill any nail holes and cracks with a suitable filler. Sand any imperfections and apply 1 coat of Easi Sealer Undercoat.

Application Method

Stir contents of can thoroughly with a wide flat stirrer ensuring the bottom of the can is reached. Apply 1 full coat of Easi Sealer Undercoat by brush, roller or spray.

Do not apply below 12°C or is likely to fall below this temperature before the paint can through dry.

Brush/Roller

Apply directly from can. Use a medium - long nap roller cover when applying by roller or use a quality bristle brush.

Spray

May be applied using conventional or airless spray. Use a 13 - 15 thou spray tip when using airless spray.



Address: 8 Manburgh Terrace
Darra Qld. 4076
Postal Address: P.O. Box 3045
Address: Darra Qld. 4076
Phone: +61 (7) 3375 3199
Facsimile: +61 (7) 3375 3886
E-mail: info@luxurypaints.com.au

Date Issued: 1 December, 2011
Page 2 of 2

LP0002

Coverage

Covers approximately 10 – 12 square metres per litre depending on porosity of surface.

Drying Times

Approximate drying times at 25°C and 50% Relative Humidity.

Touch Dries:	30 minutes
Recoat:	Minimum 2 hours.

Drying Times may be extended by adverse drying conditions or very high film build.

Cleanup

Clean all equipment promptly in water.

Properties

SOLIDS BY VOLUME:	36%
SOLIDS BY WEIGHT:	55%
WEIGHT PER LITRE:	1.4kg
GLOSS LEVEL:	7 - 10%
VOC:	approx. 30 grams per litre
DURABILITY:	Excellent - interior.

Available in white which may be tinted to pastel colours.

Resistance Properties

ABRASION:	n/a
HEAT:	Up to 60°C
SOLVENT:	Limited. Coating is sensitive to aromatic hydrocarbons, alcohols and ketones.
WATER/STEAM:	Fair. Resists mild exposure to steam and condensation.
WEATHER:	For interior use only.

Additional Information

To achieve a smooth finish, lightly sand before top-coating.